B24M

NFPA - OSHA

2- door working cover style safety cabinet for corrosives

COMPLIANCE

FM - OSHA - NFPA

ADVANTAGES

- NFPA and OSHA compliant
- FM compliant
- Storage of corrosives

BUT ALSO...

- Fixation for earthing
- Continious piano hinges
- Containment sump integrated with HDPE protection
- NFPA, OSHA and FM compliant
- Rugged construction with double wall
- Adjustable shelves in height with HDPE protection
- Integrated door handle

TECHNICAL FEATURES

Model	**B24M**	Door closure	**manual closing**
Compliance	**FM - OSHA - NFPA**	Shipping dimensions HxWxD (mm)	**1110 x 1200 x 800**
Cabinet materials	**Double wall steel structure**	Ventilation	**Both inlet and outlet**
Doors color	**blue**	Openings diameter (mm)	**50**
Number of doors	**2**	Number of compartments	**1**
Doors type	**swing doors**		**92.00**
Hinges	**right & left**	HS Code	**2147483647**

ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic and corrosive vapors (Réf : CDF-ACORG)
- Filtration box built in PVC with activated carbon filter for organic and corrosive vapors (Réf : CDF-P)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

OPTIONS

- Shelf for cabinets B24M - B24S (Réf : ESP24)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
B24M	910 x 890 x 560	710 x 795 x 455	90		1	159	92.00

Ecosafe
www.ecosafesa.com

Chemin des Champs Courbes 15
Zone industrielle de Vallaire Est
CH-1024 Ecublens (Switzerland)
www.ecosafesa.com - sales[at]ecosafesa.com