B24S

NFPA - OSHA

# 2- door working cover style safety cabinet for corrosives

## COMPLIANCE

**FM - OSHA - NFPA**

## ADVANTAGES

- NFPA and OSHA compliant
- FM compliant
- Storage of corrosives

### BUT ALSO...

- Fixation for earthing
- Continious piano hinges
- Containment sump integrated with HDPE protection
- NFPA, OSHA and FM compliant
- Rugged construction with double wall
- Adjustable shelves in height with HDPE protection
- Integrated door handle
- Self-closing doors

## TECHNICAL FEATURES

| | | | |
|---|---|---|---|
| Model | **B24S** | Door closure | **self-closing** |
| Compliance | **FM - OSHA - NFPA** | Shipping dimensions HxWxD (mm) | **1110 x 1200 x 800** |
| Cabinet materials | **Double wall steel structure** | Ventilation | **Both inlet and outlet** |
| Doors color | **blue** | Openings diameter (mm) | **50** |
| Number of doors | **2** | Number of compartments | **1** |
| Doors type | **swing doors** | | **95.00** |
| Hinges | **right & left** | HS Code | **2147483647** |

## ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic and corrosive vapors (Réf : CDF-ACORG)
- Filtration box built in PVC with activated carbon filter for organic and corrosive vapors (Réf : CDF-P)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

## OPTIONS

- Shelf for cabinets B24M - B24S (Réf : ESP24)

| Model | External dimensions HxWxD (mm) | Internal dimensions HxWxD (mm) | Storage capacity (L) | Containment sump | Shelves | Load capacity | Weight (kg) |
|---|---|---|---|---|---|---|---|
| B24S | 910 x 890 x 560 | 710 x 795 x 455 | 90 | | 1 | 159 | 95.00 |

Ecosafe
www.ecosafesa.com

Chemin des Champs Courbes 15
Zone industrielle de Vallaire Est
CH-1024 Ecublens (Switzerland)
www.ecosafesa.com - sales[at]ecosafesa.com