



## 2- door working cover safety cabinet

### COMPLIANCE

NF EN ISO 1182

### ADVANTAGES

- 2- point locking system
- NF EN ISO 1182 compliant
- Storage of flammables and toxics

### BUT ALSO...

- Containment sump at the bottom
- 2- point locking system
- Self-closing doors
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Non-flammable insulation between the walls



### TECHNICAL FEATURES

Model	<b>S604T</b>	Shipping dimensions HxWxD (mm)	<b>950 x 1200 x 800</b>
Compliance	<b>NF EN ISO 1182</b>	Ventilation	<b>Both inlet and outlet</b>
Cabinet materials	<b>12/10th epoxy painted steel structure</b>	Openings diameter (mm)	<b>100</b>
Doors color	<b>white RAL 9010</b>	Number of compartments	<b>1</b>
Number of doors	<b>2</b>	Containment sump	<b>1</b>
Doors type	<b>swing doors</b>		<b>69.00</b>
Hinges	<b>right &amp; left</b>	HS Code	<b>94032080</b>
Door closure	<b>automatic closing</b>		

### ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

### OPTIONS

- Containment sump in PVC (Réf : BP04)
- Shelf protection in PVC (Réf : EP04)
- Additional retention shelf (Réf : G04)
- Additional containment sump (Réf : GL04)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
S604T	750 x 1000 x 450	650 x 950 x 400	50		1	75	69.00