

2- door tall safety cabinet for flammables

COMPLIANCE

FM - OSHA - NFPA

ADVANTAGES

- NFPA and OSHA compliant
- FM compliant
- Storage of flammables

BUT ALSO...

- Continious piano hinges
- Containment sump at the bottom
- NFPA, OSHA and FM compliant
- Rugged construction with double wall
- Adjustable shelves in height
- Holes for the connection to the ventilation
- Integrated door handle
- Fixation for earthing
- Self-closing doors



TECHNICAL FEATURES

Model	SC60	Shipping dimensions HxWxD (mm)	1850 x 1200 x 800
Compliance	FM - OSHA - NFPA	Ventilation	Both inlet and outlet
Cabinet materials	Double wall steel structure	Openings diameter (mm)	50
Doors color	yellow	Number of compartments	1
Number of doors	2	Containment sump	1
Doors type	swing doors	HS Code	173.00
Hinges	right & left		2147483647
Door closure	self-closing		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

OPTIONS

- Shelf for cabinets MC60 - SC60 (Réf : ES60)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
SC60	1651 x 864 x 864	1537 x 781 x 771	228		2	159	173.00